

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A differential interference optical system comprising:
 - an illumination source;
 - a first polarizing element configured and arranged to convert a ray of light emitted from the illumination source into linearly polarized light;
 - a first polarizing member disposed at a first position to separate the linearly polarized light converted by the first polarizing element into two linearly polarized components which vibrate perpendicular to each other and travel at a slight separation angle;
 - an illuminating optical system configured and arranged to introduce the ray of light emitted from the illumination light source to an object to be observed;
 - a first objective lens that has a first back focal position and a second objective lens that has a second back focal position, the first objective lens and the second objective lens being arranged interchangeably with each other;
 - a second polarizing member disposed at a second position to combine the two linearly polarized components on an identical path after passing through at least one of the first objective lens and the second objective lens; and
 - a second polarizing element configured and arranged to convert a ray of light combined by the second polarizing member into linearly polarized light,
 - wherein the first polarizing member and the second polarizing member are disposed at positions different from each other in a path of rays from the illumination source to ~~said~~ the second polarizing element,
 - wherein at least one polarizing member of ~~said~~ the first polarizing member and ~~said~~ the second polarizing member possesses a position of localized fringes at which ~~said~~ the two linearly polarized components intersect with each other, and
 - wherein at least one of the first polarizing member and the second polarizing member is configured ~~so that to change~~ to change a distance therefrom to the position of localized fringes ~~is variable,~~ in accordance with an interchange between the first objective lens and the second objective lens, by ~~having~~ changing a first tilt attitude; ~~thereof while remaining disposed~~ at the first position or the second position, in reference to so that the two linearly polarized components are combined on substantially a same path even if the interchange between the first objective lens and the

second objective lens takes place, the tilt attitude being defined as an angle formed by a normal to an outside surface of the at least one of the first polarizing member and the second polarizing member and an optical axis of the first objective lens or of the second objective lens, and a second tilt attitude, at the first position or the second position, in reference to the optical axis of the first objective lens or of the second objective lens.

2. (Canceled)

3. (Withdrawn) A differential interference optical system according to claim 1, wherein each of said first polarizing member and said second polarizing member includes a combined body having two wedge-shaped prisms cemented to each other so that at least one polarizing member of said first polarizing member and said second polarizing member is rotated 180° around a rotary axis lying in a plane including an optical axis and a normal of an interface between said two wedge-shaped prisms, and thereby a distance from said at least one polarizing member to a position of localized fringes can be changed.

4. (Withdrawn) A differential interference optical system according to claim 1, wherein each of said first polarizing member and said second polarizing member includes a combined body having two wedge-shaped prisms cemented to each other so that at least one of said first polarizing member and said second polarizing member can be switched to one of a plurality of third polarizing members including combined bodies, each having two wedge-shaped prisms cemented to each other, and a switched polarizing member of said third polarizing members is rotated 180° around a rotary axis lying in a plane including an optical axis and a normal of an interface between said two wedge-shaped prisms and thereby a distance from said switched polarizing member to said position of localized fringes can be changed.

5. (Canceled)

6. (Currently Amended) A differential interference optical system according to claim 1, wherein the second polarizing member is one of a Wollaston prism and a Nomarski prism.

7. (Currently Amended) A differential interference optical system according to claim 6, wherein one of the Wollaston prism and the Nomarski prism is constructed to satisfy the following condition:

$$|\Delta\theta| \times d < 12$$

where d is a thickness of the prism, in millimeters, and $\Delta\theta$ is a variation of an angle made by a normal to a surface of the prism with the optical axis of the differential interference optical system, in degrees.

8. (Canceled)

9. (Withdrawn) A differential interference optical system according to claim 8, wherein said second birefringent element has at least one plane-parallel birefringent member.

10. (Canceled)

11. (Canceled)

12. (Withdrawn) A differential interference optical system according to claim 1, wherein a separation of an incident ray of light into two linearly polarized components vibrating perpendicular to each other and traveling at a slight separation angle and a combination of said two linearly polarized components on an identical path are achieved by one polarizing member.

13. (Withdrawn) A differential interference optical system comprising:
an illumination source;
a first polarizing element for converting a ray of light from said illumination source into linearly polarized light;
at least one polarizing member for separating an incident linearly polarized light into two linearly polarized components vibrating perpendicular to each other and traveling at a slight separation angle;
a lens system for illuminating and observing an object to be observed; and
a second polarizing element for converting incident rays of light into linearly polarized light,

wherein said at least one polarizing member possesses a position of localized fringes at which said two linearly polarized components intersect with each other, and a distance from said at least one polarizing member to the position of localized fringes is variable.

14. (Withdrawn) A differential interference optical system according to claim 2, wherein said at least one polarizing member includes a plurality of polarizing members, and said plurality of polarizing members are different in angle made by a normal of a surface of said at least one polarizing member with an optical axis of said differential interference optical system.

15. (Withdrawn) A differential interference optical system according to claim 2, wherein said at least one polarizing member is turned, with a center of rotation at a position where a phase difference between said two linearly polarized components caused by said at least one polarizing becomes zero.

16. (Withdrawn) A differential interference optical system according to claim 2, wherein said at least one polarizing member is turned, with a center of rotation at a point where a normal of a surface of said at least one polarizing member is inclined at a predetermined angle with respect to an optical axis of said differential interference optical system and said at least one polarizing member itself is moved in a direction perpendicular to the optical axis of said differential interference optical system.

17. (Withdrawn) A differential interference optical system according to claim 2, wherein said at least one polarizing member is turned, with a center of rotation at a point lying on an optical axis of said differential interference optical system, other than a point where an interface between two wedges of said at least one polarizing member intersects with the optical axis of said differential interference optical system.

18. (Withdrawn) A differential interference optical system according to claim 14, wherein wedge members constituting each of said plurality of polarizing members have identical shapes and angles.

19. (Withdrawn) A differential interference optical system comprising:
a light source;
a first linearly polarizing element;

ray separating means for reflecting or transmitting a ray of light;
a birefringent member;
an observing optical system; and
a second linearly polarizing element,
said birefringent member being rotated 180° around a rotary axis which lies in a plane including an optical axis and a normal of an interface of said birefringent member.

20. (Withdrawn) A differential interference optical system according to claim 3 or 19, wherein said rotary axis is positioned to be parallel to a surface of said member and to lie on a center line of, or separate from, said member.

21. (Withdrawn) A differential interference optical system according to claim 3 or 19, wherein said rotary axis is positioned to satisfy the following condition:

$$|\Delta\theta| \times d < 12$$

where d is a thickness of said member, in millimeters, and $\Delta\theta$ is an angle made by a normal of a surface of said member with said rotary axis, in degrees.

22. (Withdrawn) A differential interference optical system according to claim 3, wherein an angle made by a normal of a surface of said at least one polarizing member with an optical axis of said differential interference optical system can be changed.

23. (Withdrawn) A differential interference optical system according to any one of claims 3 or 19-22, wherein said first polarizing member or said second polarizing member is a Wollaston prism or a Nomarski prism.

24. (Withdrawn) A differential interference optical system according to claim 1, wherein each of said first polarizing member and said second polarizing member includes a combined body having two wedge-shaped prisms cemented to each other so that at least one polarizing member of said first polarizing member and said second polarizing member is previously rotated 180° around a rotary axis lying in a plane including an optical axis and a normal of an interface between said two wedge-shaped prisms, and thereby a distance from said at least one polarizing member to a position of localized fringes can be changed.

25. (Canceled)

26. (Currently Amended) A differential interference optical system comprising:
an illumination source;

a first polarizing element configured to convert a ray of light emitted from the illumination source into linearly polarized light;

a first polarizing member configured to separate the linearly polarized light converted by the first polarizing element into two linearly polarized components which vibrate perpendicular to each other and travel at a slight separation angle;

an illuminating optical system configured and arranged to introduce the ray of light emitted from the illumination light source to an object to be observed;

a first objective lens that has a first back focal position and a second objective lens that has a second back focal position, the first objective lens and the second objective lens being arranged interchangeably with each other;

a second polarizing member disposed at a first position, which is located on an image side of the first objective lens ~~and or the second objective lens, to combine the two linearly polarized components on an identical path after passing through the first objective lens or the second objective lens, and possessing a position of localized fringes at which the two linearly polarized components intersect with each other,~~ the second polarizing member being configured so that to change a distance therefrom to the a position of localized fringes is variable, in accordance with an interchange between the first objective lens and the second objective lens, by having changing a first tilt attitude, thereof while remaining disposed at the first position, in reference to so that the two linearly polarized components are combined on substantially a same path after passing through the first objective lens or the second objective lens even if the interchange between the first objective lens and the second objective lens takes place, the tilt attitude being defined as an angle formed by a normal to an outside surface of the second polarizing member and an optical axis of the first objective lens and a second tilt attitude, at the first position, in reference to an optical axis or of the second objective lens; and

a second polarizing element configured to convert a ray of light combined by the second polarizing member into linearly polarized light.

27. (Previously Presented) A differential interference optical system according to claim 26, wherein the second polarizing member is one of a Wollaston prism and a Nomarski prism.

28. (Previously Presented) A differential interference optical system according to claim 27, wherein one of the Wollaston prism and the Nomarski prism is constructed to satisfy the following condition:

$$|\Delta\theta| \times d < 12$$

where d is a thickness of the prism, in millimeters, and $\Delta\theta$ is a variation of an angle made by a normal to a surface of the prism with the optical axis of the differential interference optical system, in degrees.